

WONDOM ICP1 User Guide

IN-CIRCUIT PROGRAMMER FOR ADAU1701 DIGITAL SIGNAL - ICP1

By Sure Electronics Co., Ltd.



Overview

WONDOM ICP1 is an in-circuit programmer for customer programming of WONDOM products.

On-board self-boot EEPROM is included in ICP1 for operating the board independently of the Analog Devices, Inc., SigmaStudio[™] software.

The package includes: \checkmark IN-CIRCUIT PROGRAMMER FOR ADAU1701 DIGITAL SIGNAL - ICP1 x 1 \checkmark 6-pin cable x 1

Functions	Required Tools	Applicable Products
		JAB3
Programming	Analog Devices, Inc., SigmaStudio™	
		APM2

Product List

Model	SKU	Description	Basic Cables Included	
ICP1	DB-DP11219	In-circuit Programmer for ADAU1701 Digital Signal	6Pin cable x 1	
ICP3	DB-DP11224	WONDOM In-circuit Programmer with BLE Bluetooth for APP control	6Pin cable x 1	
ICP5	DB-DP11226	In-circuit Programmer with UART for PC UI Control & BLE for APP Control	6Pin cable x 1	
APM2	AA-AP23122	ADAU1701 Audio Digital Signal Processor Kernel Board		
APM3	AA-AA11428	ADAU1701 Audio Digital Signal Processor Interface Extension Kit	10Pin cable x 1	
JAB3-1100	AA-JA31181	1x 100 Watt Class D Audio Amplifier Board with Audio DSP - JAB3-1100		
JAB3-160	AA-JA31211	1 x 60 Watt Class D Audio Amplifier Board with Audio DSP - JAB3-160	Power cable x 1 Speaker cable x 1	
JAB3-250	AA-JA32172	2 x 50 Watt Class D Audio Amplifier Board with Audio DSP - JAB3-250	3.5mm AUX IN cable x 1	
JAB3-230	AA-JA32473	2 x 30 Watt Class D Audio Amplifier Board with Audio DSP - JAB3-230		

Notes:

- Represents no basic cable

Interface Definition

In this document, we will mainly give instructions on the following applications:

- How to achieve programming of APM2 / JAB3 with WONDOM ICP1 1)
- How to realize APP control of APM2 / JAB3 with WONDOM ICP1 2)

1)

2)



Open Source Files for PROGRAMMING

Products	Function	File	Version	Download	
APM2	Demonstration of Signal Flow Chart	APM2_SigmaStudio.dspproj		<u>Download</u>	
JAB3 - Mono	Demonstration of Signal Flow Chart	JAB3_SigmaStudio_MONO.dspproj		<u>Download</u>	
JAB3 - Stereo	Demonstration of Signal Flow Chart	JAB3_SigmaStudio_STEREO.dspproj		<u>Download</u>	
Note: All the "Demonstration of Signal Flow Chart" files are just for signal flow chart demonstration and customers can not use them as running programming.					

How to achieve programming of APM2/JAB3 with WONDOM ICP1?



ICP1 IN-CIRCUIT PROGRAMMER FOR ADAU1701 DIGITAL SIGNAL - ICP1

Checklist

Before starting, please make sure you have the following items on hand.



WONDOM APM2+Extension Kit (APM3)/JAB3



Analog Devices, Inc. SigmaStudio™



Quick Start

To quickly get started with the programming of WONDOM APM2 or JAB3 via ICP1, do the following steps:

Install the SigmaStuido software
 Connect ICP1 to computer
 Connect audio cables of APM2/JAB3
 Power up the audio system
 Connect ICP1 with APM2/JAB3
 Program

Click HERE to watch video.

Since the most steps of programming APM2 and JAB3 are the same, we will take APM2 as an example to show you how to operate. If there is difference or points to note, we will mark out with red words.



How to program

Be sure to follow these connection steps.



INSTALLING SIGMASTUDIO SOFTWARE CONNECTING

CONNECTING THE AUDIO CABLES

PROGRAMMING

Installing Sigmastudio software

Download the installation package for SigmaStudio software in the Analog.com. Download address is as follows. Click the EXE file and finish installation according to the prompts. <u>https://www.analog.com/en/design-center/evaluation-hardware-and-</u> software/software/ss_sigst_02.html#software-overview

SigmaStudio®

Graphical development tool for programming, developm∉ and tuning software for ADI DSP audio processors and A transceivers.

Overview Downloads And Related Software

Systems Requirements Documentation Related Har

Downloads And Related Software

View All (3) Product Downloads (1) Design Tools (1) Software Development Tools (1)

Product Downloads	
SigmaStudio Release	
Download SigmaStudio 64 Bit-OS	EXE
(Rev. 4.5)	
Download Release Notes (Rev.	PDF
4.5)	
Download SigmaStudio 64 Bit-OS	EXE
(Rev. 4.4)	
Download Release Notes (Rev.	PDF
4.4)	
NEW COLOR OF THE COLOR OF THE COLOR	

Setting up the hardware

1. Compile the needed program in advance.

 Set the SW of ICP1 at ① (PROGRAM)* and connect the ICP1 to the computer with a USB cable.
 Do not connect ICP1 with target products (APM2/JAB3) now.

3. Select "USBi" from the list on the left and drag it to the blank area on the right. Repeat the action to move "ADAU1701" and "E2Prom" to the right.

4. Please note whether the ICP1 can be recognized by the computer, if the underpainting of the "USB" turn green, it represents the ICP1 is recognized, otherwise it will ture orrange and you should reconnect the ICP1 until it turn green. See figure 1.



Connecting Audio Cables



This interface extension kit (APM3) provides three methods of audio input:

- ✓ RCA
- ✓ 3.5mm Aux
- ✓ PH-4PIN-2MM



RCA



3.5mm PH-4PIN-Headphone 2MM

Output



Use the 10 pin to 10 pin cornoid to connect APM2 with interface extension kit (APM3) for playing music.



RCA



3.5mm Aux

Input

IX PH-4PIN-2MM interface

This interface extension kit (APM3) provides three channels of audio output:

- ✓ RCA
- ✓ 3.5mm Headphone
- ✓ PH-4PIN-2MM

Powering up the board

Make sure the SW1 of APM2 is set at 1 (RUN). (Skip this step when programming JAB3)

Power up the APM2.

 Power of APM2: The DSP Kernel Board (APM2) could be powered by:
 5V micro USB through micro USB charging port (J2)
 External 5-12V DC Supply through Vin control port (J3/J4)
 External 3.3V DC Supply through +3.3V control port (J3/J4)

2. Power of Extension Kit: The Extension Kit (APM3) is powered by the Kernel Board (APM2)

Power of IC Programmer:
 WONDOM IC Programmer could be powered by:
 5V micro USB through micro USB charging port (J1)
 External 5V DC Supply from DSP Kernel Board (APM2)

Input audio signal to JAB3 and make sure the two LEDs on JAB3 are on before connecting ICP1 with JAB3. Skip this step when programming APM2.

Connect ICP1 with APM3 through 6-pin cable.

Programming

1.Click the "Link Compile Connect" (see figure 2) and you will find "Ready: Compiled" in the lower right corner of your computer.



2.Click the "Link Compile Download" (see figure 3) and you will find "Active: Compiled" in the lower right corner of your computer.



3. Make sure the SW of ICP1 is at ① (PROGRAM) and the SW1 of APM2 is at ① (RUN), and right-click the "ADAU1701" and select "Write Latest Compilation to E2PBOM" to download the program (see figure 4), then you will see a window, choose the "I2C" on the right and click "OK" (see figure 5).





Original Firmware Restore

1. Right click the "E2Prom" (see Figure 6) and click 'Read/Write Window'. You will see the following interface (Figure 7).



2. Click 'Click here to browse for file' and select firmware file (Figure 8). Then click 'Display File' like Figure 9.



Figure 8



Original Firmware Restore

3. Click 'Write Display to E2prom' then click 'OK' of the prompt box (Figure 10).



TROUBLE SHOOTING

TROUBLE	HOW TO SOLVE
ICP1 cannot be recognized by PC	 Make sure the Micro USB cable is of good quality and supports data communication Make sure ICP1 is not connected to controlled device (APM2) when connected to PC
	Make sure the ICP1 be recognized by PC
Cannot writing the program into APM2 successfully	Viake sure the icri be recognized by PC
	Make sure the SW of ICP1 is at ① (PROGRAM) and the SW1 on APM2 is set at ① (RUN)
	Make sure JAB3 is given audio signal and the two LEDs are on
Cannot writing the program into JAB3 successfully	Make sure the ICP1 be recognized by PC
	\blacktriangleright Make sure the SW of ICP1 is at $①$ (PROGRAM)
APM2 / JAB3 cannot work normally (cannot play music) under powering condition when connected with ICP1	Make sure the connection steps are correct and check the input/output cables
	Disconnect with ICP1 and re-power APM2
	Make sure the SW1 on APM2 is set at ① (RUN) (Not applicable to JAB3)